



Connecting Bracket available to connect -6.5 and -10.5 size. -13 and -16 sizes require a Base Plate for double plane configurations.

## PR NT

Ø                    2,0-6,5                    6,0-10,5                    6,0-13,0                    10,0-16,0

**TYPE**                    **PR 9-6,5 NT**                    **PR 9-10,5 NT**                    **PR 9-13,0 NT**                    **PR 9-16,0 NT**

<b>A</b>	160	212	314	344
<b>B</b>	148	200	290	320
<b>C</b>	52	65,6	82	89,5
<b>D</b>	40	52	72	80
<b>E</b>	9	12,5	25	25
<b>F</b>	296	379	469,1	559,1
<b>G</b>	23	30	40	40
<b>H</b>	70	95	135	150
<b>K</b>	100	140	200	210
<b>L</b>	314	404	519,1	609,1
<b>M</b>	9	9	17,5	17
<b>N</b>	36	47,3	58	58,5
<b>O</b>	40	50	70	90
<b>kg</b>	11	25	63	85
<b>WR</b>	40	520	72	800/GB 80 SL
<b>F [N]</b>	550	1000	1300	2000

**Richtapparat mit unterschiedlicher Rollenteilung**  
**Dresseur avec galets réglables séparément et entr'axes de galets différents**  
**Straightener with rollers separately adjustable and different roller spacing**

